

★ ★
STANDARD

Masonry saw TBE350

Cutting depth up to 110 mm



Swivelling saw head enables 45° mitre cuts



Two robust castors ensure total manoeuvrability in the deployment location



Angle stop provided for cuts of 30° to 90°

The TBE350 table saw offers an uncompromising price-performance ratio as well as high flexibility through numerous settings and application options. A sturdy saw table with

anti-slip support guarantees clean cuts. The swivelling saw head allows mitre cuts to be made with ease. Detachable table feet and transport wheels ensure trouble-free transport.

TYROLIT

System & Accessories

Technical data

Saw blade	
Max. cutting depth	110 mm
Max. saw blade Ø	400 mm
Cutting length	600 mm
Saw blade speed	2 800 rpm
Saw blade holder Ø	25.4 mm

Drive

Drive / motor	Electric
Output	2.2 kW
Standard voltage / frequency	230 V / 50 Hz
Optional voltage / frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

Design

Ininitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function (swiveling saw head)
Cap cutting function
Water tank made from powder-coated steel
Electric water pump
Dismantable

Dimensions & Weight

Length	1 140 mm
Width	640 mm
Height	1 230 mm
Weight	79 kg

System & Accessories

Masonry saw TBE350	
10981423	Masonry saw TBE350 / 230 V
10981424	Masonry saw TBE350 / 110 V