

DRIVE PPH25 ★★

Output 25 kW



Ergonomically arranged control panel



Safe due to high quality electronic components



Manometer display for main and feed cycle

The 2-stage control ensures optimum cutting speeds for all applications. A simple and uncomplicated drive

with product features reduced to the essentials.

System & Accessories



Technical data

Electric motor

Power	25 kW
-------	-------

Hydraulic

Pressure stages	2
-----------------	---

2 feed circuits	Gear wheel
-----------------	------------

Main circuit	Dual gear pump
--------------	----------------

Power

Stage 1	45 l/min at 230 bar
---------	---------------------

Stage 2	50 l/min at 200 bar
---------	---------------------

Electric

Voltage	400 V / 480 V
---------	---------------

Frequency	50 Hz / 60 Hz
-----------	---------------

Current consumption (400 V / 50 Hz)	42 A
-------------------------------------	------

Dimensions

Length	720 mm
--------	--------

Width	475 mm
-------	--------

Height	988 mm
--------	--------

Weight	145 kg
--------	--------

System & Accessories

Drive unit PPH25**

10984200*	Drive unit PPH25S / 380-420 V / 50 Hz
-----------	---------------------------------------

976206	Hose package 5pieces 8 m FD
--------	-----------------------------

975672	Hose package 2pieces 8 m FF (feed)
--------	------------------------------------

Accessories

973074	El.-plug CEE 63/5pol.
--------	-----------------------

999578	On/Off valve for wire sawing
--------	------------------------------

* Different voltage types are available upon request.