



Drive PPH25RR

Power 25 kW



Freedom of movement thanks to remote control. All remote control functions are adjustable



Three-way switch, secondary connections, operating hours counter



Plastic cover can be removed without tools

The 4-stage control ensures optimal cutting speeds for all applications and the potentiometer of the remote

control ensures a wire-conserving smooth start / soft start.



System & Accessories



Technical data

Electric motor

| | |
|-------|-------|
| Power | 25 kW |
|-------|-------|

Hydraulics

| | |
|-----------------|--------------------|
| Pressure stages | 4 |
| 2 feed circuits | Radial piston pump |
| Main circuit | Triple gear pump |

Output

| | |
|---------|---------------------|
| Stage 1 | 45 l/min at 230 bar |
| Stage 2 | 50 l/min at 200 bar |
| Stage 3 | 60 l/min at 170 bar |
| Stage 4 | 70 l/min at 140 bar |

Electrical equipment

| | |
|--|-----------|
| Voltage | 380/480 V |
| Frequency | 50/60 Hz |
| Current consumption (400 V / 50 Hz) | 42 A |
| 2 secondary connections, (230 V / 50 Hz / 10 A (400 V / 50 Hz) | |

Dimensions & Weight

| | |
|--------|----------|
| Length | 760 mm |
| Width | 550 mm |
| Height | 1 140 mm |
| Weight | 170 kg |

System & Accessories

Drive unit PPH25RR

| | |
|-----------|---|
| 10983900* | Drive unit PPH25RR / 380–420 V / 50 Hz / freq. 434 MHz |
|-----------|---|

| | |
|--------|------------------------------|
| 976206 | Hose package 5 pieces 8 m FD |
|--------|------------------------------|

| | |
|--------|-------------------------------------|
| 975672 | Hose package 2 pieces 8 m FF (feed) |
|--------|-------------------------------------|

Accessories

| | |
|--------|------------------------|
| 973074 | El.-plug CEE 63/5 pol. |
|--------|------------------------|

* Different voltage and frequency types are available upon request.