

FLOOR SAW FSD930★★

Cutting depth up to 350 mm



Easy, controlled work thanks to clear control panel



Water regulation for optimum tool cooling and useful lighting always within reach



Exact alignment of the machine using cut indicator

Thanks to intelligent weight distribution, the FSD930** features excellent cutting behaviour. The hydraulic feed

drive and electro-hydraulic cutting depth adjustment permit convenient and ergonomic operation.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	350 mm
Max. saw blade Ø	900 mm
Saw blade speed	1400 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

Drive

Drive/motor	Diesel
Type	Deutz
Output	22 kW / 30 PS
Fuel	Diesel
Fuel tank	22.8 l
Engine cooling	Air cooling
Feed	Manual
Blade drive	Via V-belt
Feed speed	0-61 m/min

Design

Electric-hydraulic cutting depth adjustment
Cutting depth indicator
Tool cooling using water fork
Left/right cutting function
Corner flush cutting function

Dimensions & Weight

Length	1170 mm
Width	820 mm
Height	1250 mm
Weight	655 kg

System & Accessories

Floor saw FSD930***	
10984042	Floor saw FSD930***
Accessories	
10984390	Green concrete kit with 450 mm blade guard and transformation set (2300 rpm)

Diesel particle filter and transformation set on request.