

FLOOR SAW FSE1240★★


Cutting depth up to 480 mm



Suitable for construction site use, intelligent design with protected electronic components



Constant control and monitoring possibility thanks to precise displays



Easy handling due to logically arranged control panel

Thanks to intelligent weight distribution, the FSE1240** features excellent cutting behaviour. The hydraulic feed drive and electro-hydraulic cutting depth adjustment ensure convenient

and ergonomic operation. Increased flexibility using left- and right-handed cutting function and corner cutting function.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	480 mm
Max. saw blade Ø	1200 mm
Saw blade speed	1075 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

Drive

Drive/motor	Electric
Output	30 kW
Voltage/frequency	400 V / 50 Hz
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-61 m/min.

Design

Electro-hydraulic cutting depth adjustment
Cutting depth indicator
Tool cooling using water fork
Left/right cutting function
Corner flush cutting function

Dimensions & Weight

Length	1,700 mm
Width	870 mm
Height	1,160 mm
Weight	840 kg

System & Accessories

Floor saw FSE1240**	
10984045	Floor saw FSE1240S

Diesel particle filter and transformation set on request